



# AQUATROL

## PRODUCT DATA

### CC-2700

#### APPLICATION:

MOMAR AQUATROL CC-2700 is a concentrated, liquid dispersant and anti-foulant for use in the treatment of recirculating cooling water systems such as cooling towers, heat exchangers, etc. This product will effectively disperse compacted deposits which may cause congestion and inefficient heat transfer, thereby allowing removal from the system by bleed, flushing or draining. Normally, this product is used in conjunction with the appropriate Aquatrol corrosion and scale inhibitor in systems subject to heavy soil loading, or to clean existing deposits, since corrosion and deposit control are more effectively achieved on clean system surfaces.

#### PRODUCT PROPERTIES:

Physical State: Clear Liquid  
pH: 7.6  
Density: 1.17 gm/cc  
Solubility: Complete in water

#### DOSAGE RATE:

This product is shot fed to system at a rate proportional to severity of problem. Generally, it is fed at a rate of **one litre per 8000 litres** system volume per day or in a fixed ratio to Aquatrol corrosion and scale inhibitor product requirement as recommended by Aquatrol Technical Service. No control tests are required.

#### HANDLING:

Keep from freezing and extreme heat.

#### SAFETY DATA:

Keep container closed when not in use. Avoid contact with other chemical materials. Keep from freezing. This product contains alkali which may cause burns to skin and eyes. Do not get in eyes, on skin or on clothing. Do not take internally. In case of contact with skin or eyes, flush with plenty of water and if irritation persists, get medical attention immediately.

#### PACKAGING:

Shipped in non-returnable steel lined drums.

### Quality Aquatrol Products

P O Box 2257 CLAREINCH 7740

Tel Toll Free: 0800 012 053

PROVIDING PRODUCTS OF MOMAR AQUATROL RESEARCH  
IN THE U.S.A., CANADA, EUROPE AND AFRICA

MOMAR



ATLANTA PLANT