



TECHNICAL DATA REPORT



Correspondence Address:

P O Box 2257
CLAREINCH
7740

FROM THE RESEARCH &
DEVELOPMENT LABORATORIES
OF MOMAR, INC.

Grand

Description:

A combination of new ingredients which are totally exclusive to Momar. Grand provides durability that resists scuffing, eliminates rubber marking, provides detergent resistance, and re-coats and spray buffs easily.

Benefits:

- * Eliminates floor finish problems of the past.
- * 50 - 60 square meters coverage area per litre.
- * Features gloss that gives your floor that "wet" look.
- * Designed for all resilient floors: rubber, asphalt tile, vinyl, and linoleum.
- * Recommended finish for terrazzo floors previously sealed with Momar's Majestic.

Application:

Floor Care Directions: Strip floors thoroughly with Exit. Apply two full, even coats of Grand. Allow 30 - 40 minutes drying time between coats.

Floor Maintenance Directions: Keep dirt, sand, and grit off floors with daily sweeping. Mop as necessary with Refresh. Use Safe! or Firstmate at a dilution of 1 in 200 for germicidal/disinfecting. Let floor air dry. Spray buff will bring back shine. Use either Enliven or Refresh as needed. Re-coat with Grand. After cleaning, touch-up traffic lanes or re-coat entire floor. Always allow the floor to dry thoroughly before allowing foot traffic.

Specifications:

pH @ 25°C (ASTM-E-70)	8.5 - 9.0
Density @ 25°C (ASTM-D-287)	1.025 gm per cc
Color (visual)	White
Appearance @ 25°C (visual)	Opaque Emulsion
Percent Solids (140°C for 40 min)	25
Coverage	50 to 60 square meters per litre
Slip Resistance	Coefficient of Friction of 0.52
Health / Flammability / Reactivity	0 / 0 / 0
Personal Protection	A - Safety glasses

MOMAR

8 Induland Crescent, Lansdowne, Cape Town
Tel: 021-6921295 Fax: 021-6913898 Toll Free: 0800 012053
Email: orders@momar.co.za