

IVORY 2222

HIGH TEMPERATURE ALL PURPOSE FOOD GRADE GREASE

LuBest Ivory 2222 is an all purpose food grade grease approved HI for incidental contact for all food processing equipment by the USDA. Ivory 2222 is extremely shear stable and has excellent resistance to water washout. Ivory 2222 pumps easily at low temperatures and remains effective down to 0°F (-18°C) and at maximum continuous temperatures up to 250°F (120°C) and intermittent temperatures up to 300°F (149°F).

U.S.D.A. Authorized	HI
NLGI Consistency	No. 2
Worked Penetration @ 77°F, ASTM D-217	
Worked 60 Strokes265-295
Worked 10,000 Strokes295
Worked 55,000 Strokes295
Dropping Point, °F500°F (260°C)
Viscosity Base Oil	
Viscosity, SUS @ 100°F325-375
Viscosity Index80
Pumpable Down to0°F (-18°C)
Operating Range0°F to 250°F (-18°C to 121°C)
Intermittent Periods300°F (149°C)
Oil Separation, % ASTM D-1742005
Oxidation Stability, 50 lbs. Pressure Drop, 100 hours, PSI-ASTM D-9424
Roll Stability, 2 Hours ASTM D-18310025
Wheel Bearing Test, 6 Hours @ 235°F ASTM D-1263No Leakage
Rust & Corrosion Test, ASTM D-1743#1 Rating
Water Washout, ASTM D-1264	
% Loss @ 100°FNone
% Loss @ 175°FNone
Timken OK Load, lbs., ASTM D-250935
Type	Calcium Complex
Texture	Smooth & Tacky
ColorWhite
FDA ComplianceTitle 21, Code of Federal Regulations 178.3570

MOMAR

LUBEST