

# IVORY 3333

## HIGH TEMPERATURE ALL PURPOSE FOOD GRADE GREASE

LuBest Ivory 3333 is a high temperature all purpose food grade grease approved HI for incidental contact for all food processing equipment by the USDA. It is extremely shear stable and has excellent resistance to water washout. This makes Ivory 3333 an excellent choice in areas subject to wash down and sanitization procedures.

U.S.D.A. Authorized .....	HI
NLGI Consistency .....	No. 2
Worked Penetration @ 77°F, ASTM D-217	
Worked 60 Strokes .....	.265-290
Worked 10,000 Strokes .....	.290
Worked 55,000 Strokes .....	.290
Dropping Point, °F .....	.500°F (260°C)
Viscosity Base Oil	
Viscosity, SUS @ 100°F .....	.325-375
Viscosity Index .....	100
Pumpable Down to .....	-.20°F (-29°C)
Operating Range .....	.20°F to 500°F (-29°C to 260°C)
Intermittent Periods .....	.550°F (288°C)
Oil Separation, % ASTM D-1742 .....	.005
Oxidation Stability, 50 lbs. Pressure Drop, 100 hours, PSI-ASTM D-942 .....	.4
Roll Stability, 2 Hours ASTM D-1831 .....	.0025
Wheel Bearing Test, 6 Hours @ 235°F ASTM D-1263 .....	No Leakage
Rust & Corrosion Test, ASTM D-1743 .....	#1 Rating
Water Washout, ASTM D-1264	
% Loss @ 100°F .....	None
% Loss @ 175°F .....	None
Timken OK Load, lbs., ASTM D-2509 .....	.35
Four-Ball E.P. Test, ASTM D-2596	
Load Wear Index .....	.50
Seizure .....	122
Weld .....	250
Type .....	Aluminum Complex
Texture .....	Smooth & Tacky
Color .....	Transparent Amber
FDA Compliance .....	.21CFR178.3750

**MOMAR**

**LUBEST**