

NOX SMOKE

ULTRA HEAVY-DUTY ALKALINE CLEANER AND DECARBONIZING DEGREASER



DESCRIPTION

High alkaline, low-foaming, industrial strength degreaser. Rips off carbon and baked on grease in seconds. Just spray on and wipe off.

BENEFITS

- Non-Flammable
- Ready-To-Use
- Eliminates scrubbing
- USDA A2
- Unscented

FOR USE ON

- Smoke houses*
- Greasy Equipment*
- Stove Tops*
- Grills*
- Griddles*
- Processing Utensils*
- Porcelain Counters*
- Burners*
- Pots & Pans*
- Smoke trees*
- Ovens*
- Rotisseries*
- Racks*
- Drip Pans*
- Stainless Steel*
- Concrete Floors*
- Hoods*
- Ceramic Ware*



APPLICATIONS

Oven Cleaning Directions

1. For ease of application, remove racks and clean separately.
2. NOX SMOKE works on hot and cold ovens. For best results, pre-heat oven to 90 deg C then turn off.
3. From a distance of 20 to 30 cm, spray or foam a liberal amount of NOX SMOKE on all oven surfaces to be cleaned.
4. Allow to stand 1-2 minutes on warm ovens and 3-4 minutes on cold ovens. Scrub with coarse pad if necessary.
5. Rinse thoroughly and repeat where needed.
6. Wipe dry with a clean cloth.
7. After cleaning, heat oven for at least 10 minutes before using.

General Cleaning Directions

Add the required amount of NOX SMOKE as per the dilution chart below.

Application Method	Water Dilution	Operating Temperature	Contact Time, Min.	Rinsing
Hand Brush	50 - 70 ml/litre	30 - 40 deg C	3 - 5	Water
Low Pressure Spray	30 - 50 ml/litre	50 - 60 deg C	5 - 10	Water
High Pressure Spray	15 - 30 ml/litre	75 - 80 deg C	1/2 - 1	Water
Steam Cleaning	10 - 15 ml/litre	75 - 80 deg C	1/2 - 2	Water
Soak Cleaning	50 - 70 ml/litre	60 - 80 deg C	15 - 4 hrs.	Water
Mechanical Washers	30 - 50 ml/litre	75 - 80 deg C	30 - 2 hrs.	Water

SPECIFICATIONS

pH @ 25°C (ASTM-E-70)
 Density @ 25°C (ASTM-D-287)
 Color (visual)
 Appearance @ 25°C (visual)
 Foam Height
 Odor
 Health/Flammability/Reactivity
 Personal Protection

14.0
 1.46 g/mL
 Water white
 Clear
 Low
 Unscented
 3 / 0 / 1
 C - Safety glasses, gloves, apron

MOMAR®

MOMAR

8 Induland Crescent, Lansdowne, Cape Town
 Tel: 021-6921295 Fax: 021-6913898 Toll Free: 0800 012053
 Email: orders@momar.co.za