

### Description:

A concentrated, non-flammable, water displacing, penetrating lubricant for use on bolts, nuts, screws, and metal parts that have been corroded and frozen together.

### Benefits:

- Safe on ferrous and non-ferrous metals.
- Not listed by OSHA or NTP as a carcinogen.
- Has a high dielectric strength of greater than 11,000 volts.
- Has no flash point – completely non-flammable.
- Contains no ozone depleting chemicals or CFCs.
- Meets or exceed the following specifications:
  - 0-2-001284B (water displacing compounds)
  - MIL-C-81309 (clear corrosion preventatives)
  - MIL-C-161730 Grade 3 (corrosion preventative compounds)
- Contains no 1,1,1-Trichloroethane and is a recommended replacement under the EPA's SNAP program.
- Provides a rust-inhibiting barrier to protect metal from destructive corrosive elements. This enables equipment to run smoother, look better, and last longer.



### Safe For Use On:

- Air conditioners
- Automobiles
- Battery terminals
- Bearings
- Cables
- Carburetor linkages
- Chains
- Compressors
- Conveyors
- Dies
- Drills
- Drawers
- Electrical Motors
- Fans
- Farm Equipment
- Flanges
- Lathes
- Locks & Hinges
- Nuts & Bolts
- Outboard Motors
- Parking Meters
- Power Generators
- Pumps
- Reels
- Screws
- Snow removers
- Springs
- Studs
- Switches
- Traffic signals
- Typewriters
- Vending Machines
- Windows
- Windshield wipers
- Wire rope cables
- Work shop tools

### Application:

Shake well before using. Hold can 20 to 30 cm from surface to be sprayed. For best results, use short spray bursts. Reapply as needed.

\*Pretest in an inconspicuous place on plastics before use.

### Specifications:

pH @ 25°C (ASTM-E-70)

Density @ 25°C (ASTM-D-287)

Evaporation

Appearance (visual)

Odor

Dielectric Strength

Health/Flammability/Reactivity

Personal Protection

7.0

1.62 g/mL

Fast

Clear, thin

Coconut

>11,000 volts

2 / 1 / 0

G - Safety Glasses, Gloves, Respirator

# MOMAR

# MOMAR