

OUTA-SIGHT

MULTI-PURPOSE NON-STAINING FOOD GRADE GREASE IN AEROSOL

LuBest Outa-Sight quickly forms into a thick clinging transparent grease.

LuBest Outa-Sight is a high temperature all purpose food grade grease approved HI for incidental contact for all food processing equipment by the USDA. It is extremely shear stable and has excellent resistance to water washout. This makes Outa-Sight an excellent choice in areas subject to wash down and sanitization procedures.

U.S.D.A. Authorized	HI
NLGI Consistency	No. 2
Worked Penetration @ 77°F, ASTM D-217	
Worked 60 Strokes265-290
Worked 10,000 Strokes290
Worked 55,000 Strokes290
Dropping Point, °F500°F (260°C)
Viscosity Base Oil	
Viscosity, SUS @ 100°F325-375
Viscosity Index	100
Pumpable Down to	-20°F (-29°C)
Operating Range	20°F to 500°F (-29°C to 260°C)
Intermittent Periods550°F (288°C)
Oil Separation, % ASTM D-1742005
Oxidation Stability, 50 lbs. Pressure Drop, 100 hours, PSI-ASTM D-9424
Roll Stability, 2 Hours ASTM D-18310025
Wheel Bearing Test, 6 Hours @ 235°F ASTM D-1263	No Leakage
Rust & Corrosion Test, ASTM D-1743	#1 Rating
Water Washout, ASTM D-1264	
% Loss @ 100°F	None
% Loss @ 175°F	None
Timken OK Load, lbs., ASTM D-250935
Four-Ball E.P. Test, ASTM D-2596	
Load Wear Index50
Seizure	122
Weld	250
Type	Aluminum Complex
Texture	Smooth & Tacky
Color	Transparent Amber
FDA Compliance21CFR178.3750

