

SILICONE SPRAY

**WATERPROOFING LUBRICANT & SILICONE RELEASE AGENT
FOR THE PROCESSING & PACKAGING INDUSTRY**

DESCRIPTION

Prevents sticking with a high concentration of dry silicone. Retards corrosion and provides lubricity while ending "poly build-up." Heat stable silicone release agent for the processing and packaging industry will not freeze or melt.

BENEFITS

- Ends "poly build-up" on the mandrels, transfer chutes, and guide rails. Prevents jamming and production slowdown.
- Stop sticking of drawers, windows, door screens, zippers, and locks
Eliminates annoying squeaks in hinges, latches, springs, etc. Stops car doors, locks, and trunk moldings from sticking.
- Retards corrosion - protects battery terminals, tools, guns, skates, aluminum windows and doors, etc. Waterproofs ignition systems and spark plugs.
- Dries fast - leaves no greasy or oily film
- Will not freeze or melt.
- Not affected by water and oil.
- Colorless, stainless, and waxless.
- Contains No 1,1,1 Trichloroethane.

***Safe on all surfaces:
metal, glass, rubber, plastic,
painted finishes, and fabrics.***

APPLICATION

Thoroughly clean the surface to be sprayed. Spray a light film with a sweeping motion. When used on sticky surfaces, work object back and forth. Spray again if necessary. Maybe used on equipment containing fresh, frozen, or baked food products.

SPECIFICATIONS

pH @ 25°C (ASTM-E-70)	Neutral, non-polar solvent
Density @ 25°C (ASTM-D-287)	0.7 g/mL
Color (visual)	None
Appearance @25°C (visual)	Clear
Foam Height	None
Odor	Low Solvent Odor
Health/Flammability/Reactivity	1/4/0
Personal Protection	B - Glasses and Gloves
Container	500 ml can

MOMAR®

MOMAR

8 Induland Crescent, Lansdowne, Cape Town
Tel: 021-6921295 - Fax: 021-6913898
info@momar.co.za - www.momar.co.za