

# TITAN 888

## ALL PURPOSE WATER RESISTANT GREASE

LuBest Titan 888 All Purpose Water Resistant Grease has an aluminum complex base to provide excellent water resistance and contains extreme pressure additives to provide extra protection.

U.S.D.A. Authorized .....	H2
NLGI Consistency .....	No. 2
Worked Penetration @ 77°F, ASTM D-217	
Worked 60 Strokes .....	.275-.295
Worked 10,000 Strokes .....	.285
Worked 55,000 Strokes .....	.285
Dropping Point, °F .....	.500°F (260°C)
Viscosity Base Oil	
Viscosity, SUS @ 100°F .....	.1075-1.125
Viscosity Index .....	.85
Pumpable Down to .....	-.0°F (-18°C)
Operating Range .....	.5°F to 500°F (-15°C to 260°C)
Intermittent Periods .....	.550°F (288°C)
Oil Separation, % ASTM D-1742 .....	.005
Oxidation Stability, 50 lbs. Pressure Drop, 100 hours, PSI-ASTM D-942 .....	.2
Roll Stability, 2 Hours ASTM D-1831 .....	.0025
Wheel Bearing Test, 6 Hours @ 235°F ASTM D-1263 .....	No Leakage
Rust & Corrosion Test, ASTM D-1743 .....	.#1 Rating
Water Washout, ASTM D-1264	
% Loss @ 100°F .....	.None
% Loss @ 175°F .....	.None
Timken OK Load, lbs., ASTM D-2509 .....	.50
Four-Ball E.P. Test, ASTM D-2596	
Load Wear Index .....	.50
Seizure .....	.130
Weld .....	.280
Four-Ball Wear Test (20Kg, 1800 RPM, 130°F, 1 Hour) ASTM D-2266	
Coefficient of Friction .....	.009
Scar Diameter, mm .....	.0251
Type .....	.Aluminum Complex
Texture .....	.Smooth & Tacky
Color .....	.Amber

**MOMAR**

**LUBEST**