

TITAN 888

ALL PURPOSE WATER RESISTANT GREASE

LuBest Titan 888 All Purpose Water Resistant Grease has an aluminum complex base to provide excellent water resistance and contains extreme pressure additives to provide extra protection.

U.S.D.A. Authorized	H2
NLGI Consistency	No. 2
Worked Penetration @ 77°F, ASTM D-217	
Worked 60 Strokes275-.295
Worked 10,000 Strokes285
Worked 55,000 Strokes285
Dropping Point, °F500°F (260°C)
Viscosity Base Oil	
Viscosity, SUS @ 100°F1075-1.125
Viscosity Index85
Pumpable Down to	-.0°F (-18°C)
Operating Range5°F to 500°F (-15°C to 260°C)
Intermittent Periods550°F (288°C)
Oil Separation, % ASTM D-1742005
Oxidation Stability, 50 lbs. Pressure Drop, 100 hours, PSI-ASTM D-9422
Roll Stability, 2 Hours ASTM D-18310025
Wheel Bearing Test, 6 Hours @ 235°F ASTM D-1263	No Leakage
Rust & Corrosion Test, ASTM D-1743#1 Rating
Water Washout, ASTM D-1264	
% Loss @ 100°FNone
% Loss @ 175°FNone
Timken OK Load, lbs., ASTM D-250950
Four-Ball E.P. Test, ASTM D-2596	
Load Wear Index50
Seizure130
Weld280
Four-Ball Wear Test (20Kg, 1800 RPM, 130°F, 1 Hour) ASTM D-2266	
Coefficient of Friction009
Scar Diameter, mm0251
TypeAluminum Complex
TextureSmooth & Tacky
ColorAmber

MOMAR

LUBEST