

TITAN 999

NON-MELT GREASE

LuBest Titan 999 Non-Melt Grease has a Bentone base to provide non-melt characteristics and contains extreme pressure additives to provide extra protection.

NLGI Consistency	No. 2
Worked Penetration @ 77°F, ASTM D-217	
Worked 60 Strokes255-285
Worked 10,000 Strokes285
Worked 55,000 Strokes285
Dropping Point, °F	None
Viscosity Base Oil	
Viscosity, SUS @ 100°F	1475-1525
Viscosity Index	105
Pumpable Down to	-0°F (-18°C)
Operating Range5°F to 500°F (-15°C to 260°C)
Intermittent Periods700°F (371°C)
Oil Separation, % ASTM D-1742005
Oxidation Stability, 50 lbs. Pressure Drop, 100 hours, PSI-ASTM D-9423
Roll Stability, 2 Hours ASTM D-18310025
Wheel Bearing Test, 6 Hours @ 235°F ASTM D-1263	No Leakage
Rust & Corrosion Test, ASTM D-1743	#1 Rating
Water Washout, ASTM D-1264	
% Loss @ 100°F	None
% Loss @ 175°F	None
Timken OK Load, lbs., ASTM D-250955
Four-Ball E.P. Test, ASTM D-2596	
Load Wear Index50
Seizure122
Weld250
Four-Ball Wear Test (20Kg, 1800 RPM, 130°F, 1 Hour) ASTM D-2266	
Coefficient of Friction009
Scar Diameter, mm0251
Type	Bentone
Texture	Smooth & Tacky
Color	Red

MOMAR

LUBEST